

Product	Min. Cylinder Volume	Approx. Tare Wgt. w/ Valve (w/o Cap)	OD	Height w/o Valve and Cap	Height w/ Valve and Cap	tmin	Solvent Acetone	Acetylene Capacity
	(in ³)	(lb)	(in)	(in)	(in)	(in)	(lb)	(ft ³)
S-10	125	8.2	4	13.375	15.4	0.07	1.3	10
S-40	466	23.7	6.2	19.813	23.2	0.092	5.1	40
S-40BF	466	26.5	6.2	20	25.912	0.092	5.1	40
S-75	855	43.8	7.2	25.5	31.26	0.1	9.3	75
S-100	1055	55.6	7.2	30.75	36.6	0.129	12.4	100
S-145	1536	74.3	8.2	34.25	38.2	0.13	25.9	145
WM-210	2194	101.9	10.3	32.6	38.2	0.13	25.9	210
WM-250	2606	119	10.3	38	43.6	0.13	30.8	250
W-310	3240	136.65	12.3	32.75	38.35	0.134	38.2	310
W-397	4151	169.8	12.3	41	46.66	0.134	49	397
W-420	4375	177.1	12.3	43.25	48.85	0.134	51.9	420
W-450	4680	184.9	12.3	45.25	50.85	0.134	55.6	450